



VARISPIN 4A

Compact centrifuge specific for frequent application

STANDARD SPECIFICATION



Description	VARISPIN 4A
Max. RPM	4,000rpm
Max. RCF	2,075 xg
Max. Capacity	15ml x 8
Accel Decel time to max rpm	20sec / 20sec
Noise Level	≤60dB
Set Time	99 min 59 sec or continuous
Time Count	From start / From set-up RPM
Program	10 memory
Display	Blue LCD
RPM Range	400 to 4,000 RPM
Display Message on screen	RPM(RCF), Time, Program
Available Rotor Quantity	1
Power Supply	AC 230V ± 10%, 50-60Hz, 1Phase
Power Consumption	0.15KW
Dimension(W x D x H)	291 x 416 x 244mm(H:550mm with open lid)
Weight (without rotor)	14kg
Cat. No.	CS-C-D4A-SET
For 110V, 50-60Hz	CS-C-D4A-SET_V1

MAIN FEATURE



Compact Design

With the smallest floor area in its class, space can be arranged more freely on a complex experiment table that use multiple equipments.



LCD screen with high visibility











SOFT CLOSING
DOOR LOCK



Silent Operation

AVAILABLE ANGLE ROTORS

	AL815D	F15A-3	F15A-5			
						
Fixed Angle rotor $\angle 40^\circ$ 8 x 15ml Radius(mm) : 116						
Volume (ml)		3	5	10	15	15 Conical
Number per rack / rotor		8	8	8	8	8
Adaptor bore (mm)		13.5	13.5	18.0	18	18
Max. height for use (mm)		120	142	131	131	131
RPM		4,000	4,000	4,000	4,000	4,000
Radius (mm)		97.4	114.3	116	116	110.2
RCF		1,742	2,045	2,075	2,075	1,971

ORDER INFORMATION

	ITEM	DESCRIPTIONS	Cat. No.
Set	VARISPIN 4A Set	230V \pm 10%, 50-60Hz, 1Phase, Eu Plug, 291x416x244mm, 14Kg Including AL815D rotor	CS-C-D4A-SET
	VARISPIN 4A Set	110V \pm 10%, 50-60Hz, 1Phase, Eu Plug, 291x416x244mm, 14Kg Including AL815D rotor	CS-C-D4A-SET_V1